

2013/2415 Bandsaw



The Gold Standard Since 1921.®

POWERMATIC®

2013/2415 Bandsaw

FEATURES

Powerful, totally enclosed, fan cooled motor — keeps out dust for longer life and maximum performance

Extra large cast iron table offers more work area in front of the blade

Table tilts 45° to the right and 10° to the left, and comes standard with a T-slot miter gauge

Cast iron drive wheels are balanced and equipped with vulcanized rubber tires for positive blade tracking

Lower wheel brush eliminates sawdust buildup

Convenient foot brake for rapid stops

Fully adjustable blade guard

4" dust collection port for connection to workshop dust collection system

Two speed drive pulley

Extra wide flange and heavy-duty trunnion assembly provides extra durability while eliminating any flexing of the table



New Crank handle tilts Table 45° right and 10° left

Model	2013	2415
Stock Number (2HP, 1Ph, 230V)	1791257	N/A
Stock Number (3HP, 1Ph, 230V)	N/A	1791259
Stock Number (3HP, 3Ph, 230/460V*)	1791258	N/A
Stock Number (5HP, 3Ph, 230/460V*)	N/A	1791260
Blade Speeds (SFPM)	2000 and 4000	2000 and 4000
Thickness Capacity, Maximum (in.)	12-3/8	14-3/8
Width Capacity, Maximum (in.)	20	24
Table Size (in.)	24 x 24	24 x 28
Table Tilt (deg.)	45 right, 10 left	45 right, 10 left
Approximate Blade Length (in.)	158-1/2	180-1/2
Blade Widths (min., max. / in.)	1/4, 1-1/2	1/4, 1-1/2
Switch	Magnetic	Magnetic
Dust Collection Minimum CFM Required	600	600
Table Height at 90° (in.)	35-1/4	35-3/8
Floor Space Required (in.)	39 x 45-1/2	39 x 51-1/2
Shipping Weight (lbs.)	970	1190

**Pre-Wired 230Volt*

GM DISTRIBUTOR LLC.
Barre, VT USA
www.copylathe.com
1-802-476-8354

POWERMATIC®
The Gold Standard Since 1921.®

STOCK NO. 900840
Printed in the U.S.A.
©2005 WMH TOOL GROUP, INC.
All rights reserved.